

# ***Dynamic 2000***

## **Manual sealless steel strapping tool**

---



### **Characteristics**

---

|                        |   |
|------------------------|---|
| Strapping qualities:   | Regular duty max. 850 N/mm <sup>2</sup> / 123'000 psi |
| Strapping dimensions:  |   |
| widths                 | 12.7 – 20.0 mm / ½ - ¾"                               |
| thicknesses            | 0.38 – 0.58 mm / .015 – .023"                         |
| Weight:                | 3.9 kg / 8.6 lbs                                      |
| Average seal strength: | approx. 80 %  |

### **Advantages**

---

- Quality light weight sealless combination tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages)
- Permits a very easy and efficient operation and outperforms other strapping tools by its ruggedness and its high reliability
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals

# Dynamic 2000

## Chart of types Dynamic 2000

---

| Item No. | Model                       | Regular duty steel strapping<br>max. 850 N/mm <sup>2</sup> / 123'000 psi |      |             |           |
|----------|-----------------------------|--|------|-------------|-----------|
|          |                             | Width  |      | Thicknesses |           |
|          |                             | mm   | inch | mm          | inch      |
| 13.2307  | Dynamic 2000/12.7/0.38-0.58 | 12.7   | ½"   | 0.38-0.58   | .015-.023 |
| 13.2308  | Dynamic 2000/13/0.38-0.58   | 13.0   |      | 0.38-0.58   | .015-.023 |
| 13.2309  | Dynamic 2000/16/0.38-0.58   | 16.0   | 5/8" | 0.38-0.58   | .015-.023 |
| 13.2311  | Dynamic 2000/19/0.38-0.58   | 19.0   | ¾"   | 0.38-0.58   | .015-.023 |
| 13.2312  | Dynamic 2000/20/0.38-0.58   | 20.0   |      | 0.38-0.58   | .015-.023 |